Hangler 2-aks 3-vejs 11,8T Tipkærre, Tipper



Poulsen Biler ApS Haarup skovvej 7, Haarup 8600 Silkeborg

Sælger Philip K. Bredahl philip@poulsenbiler.com

- +45 74 67 11 12
- +45 28 90 01 31

and the state of t	and the second of the second		
Basis			
Туре	Drawbar		
Aksel	2		
Stand	Ny		
Registration			
Year	2024		
Ref. no.	7119		
Brakes			
Drum brakes	~		
Incoupling			
Electrical coupier	2x7-polet		
Air- coupier	DuoMatic		

ú	りよりようようなら		
	Chassis		
	Total axle load	10	0.900kg
	Axle type		BPW
	Airsuspension		~
	Kingpin pressure		900kg
	Total length	7.	000mm
	Drawbar height	750-1.	050mm
	Tyres		
	Dimensions	235/75	R17,5"
	1st axle tyres L-F	R% 1	00-100
	2nd axle tyres L-	R% 1	00-100

Weight	
Loading capacity	8.640kg
Total weight	11.800kg
Empty weight	3.160kg
truck body / box	
Bottom	Stål
Side board	✓
Front board	v
Height of side board	450mm
Tie-down rings in botton	n 🗸
5 ton lashing eyes	10 stk.
Length inside	5.000mm
Inside width	2.420mm

Beskrivelse

FABRIKSNY SMALL AND SMART 11, 8T HANGLER 3-WAY TIPCART!

3-Way Tip via 1-string hydraulic from the tractor. (Backtip + page tips for both sides)

The cart is equipped with BPW axles with drum brakes on parabolic springs.

The base is constructed of steel, with removable steel sides + steel tailgate. The front is bolt mounted and can also be removed if desired.

The sides are equipped with spring-features as seen on the front, which makes it simple for a person to open and close the sides without difficulty.

- 2 pcs loose 8,000 kg (pair) 3,000 x 360mm alu ramps stored in the tray between the chassis rails-are pulled out at the back of the cart.
- 1,750 mm long drawbar with 57mm wooden bunk. The drawbar is height adjustable. Galvanized chassis.

For further information call or write to us:

+ 45 7467 1112/philip@poulsenbiler.com



















